

SAFETY FIRST

INTRODUCING THE NEW AND IMPROVED RFD SEASAVA PRO-ISO LIFERAFT

The RFD Seasava Pro-ISO Liferaft encompasses everything that the RFD brand stands for - a quality product, offering unparalleled safety coupled with real value for money.

Through extensive research and development, we have further improved the structure and performance of the RFD Seasava Pro-ISO Liferaft. Providing a more compact, lightweight raft allowing minimum deck space for storage. Aimed at complementing our already renowned lifejacket and lifesaving equipment range, the RFD Seasava Pro-ISO Liferaft is the ideal liferaft solution developed specifically for the leisure market.

Manufactured to the same high specifications as all RFD safety products, our new sleek, lightweight, compact container takes up little deck space. Meeting the stringent ISO 9650-1 standard for inflatable liferafts, the RFD liferaft is one of the most compact, robust and durable leisure liferafts available on the market today.



KEY BENEFITS

Reassurance

- Extended service period of 3 years, reducing your ongoing costs
- Manufactured from long lasting corrosion and abrasion resistant lightweight PU material
- Confidence assured with a deployment time of just 40 seconds

Dependable

- High volume water pockets to ensure maximum stability when inflated
- Simple to close canopy is manufactured to the highest standards, providing added protection from the elements
- Semi-rigid boarding ramp allows for quick, easy and safe boarding
- Interior and exterior lifelines help occupants stabilise themselves during heavy seas
- Exterior pressure relief valves ensure excess CO₂ is not released into the liferaft
- Vacuum packed into corrosion resistant containers for prolonged durability
- Comes with the following emergency pack options: <24, >24 or SOLAS B pack

Visibility

- Orange high visibility canopy and buoyancies with retro-reflective panels to help speed up the search and rescue process
- Canopy fitted with internal and external strobing light to ensure optimum visibility

Flexible

- Available in two packaging options – a weather proof valise or a tough, lightweight container

Global Service

- Can be serviced by our network of over 580 Survitec Group fully approved stations

Compact

- Revolutionary container design, developed in conjunction with an award-winning design house, is not only aesthetically pleasing but lightweight and compact taking up minimum deck space
- New design features include handles to ensure ease of manoeuvrability and a document holder to allow the inclusion of important certificates and servicing documents

WEIGHTS & DIMENSIONS

Equipment

Item list	ISO9650		SOLAS
	<24hrs	>24hrs	
Rescue line & quoit	1	1	1
Floating knife	1	1	1
Bailer	1	1	1
Sponges	2	2	2
Floating anchor	1	1	2
Paddles	2	2	2
First aid kit	1	1	1
Signalling whistle	1	1	1
SOLAS approved red parachute flares	2	2	2
SOLAS approved red hand flares	3	6	3
Smoke signals	-	-	1
Watertight torch with spare batteries and bulb	1	2	1
Radar reflector	-	-	1
Signalling mirror	1	1	1
Distress signal table	1	1	1
Food rations	-	10,000kj per person	-
Water rations	-	1.5 ltr per person	-
Anti-seasickness tablets	6 per person	6 per person	6 per person
Seasickness bags	1 per person	1 per person	1 per person
Survival instructions	1	1	1
Immediate action leaflet	1	1	1
Thermal protective aids	-	2	2
Repair kit	1	1	1
Bellows	1	1	1

Container Dimensions

Liferaft size	Pack	ABS CONTAINER DIMENSIONS			Weight (kg)
		Size (mm)			
4	<24	800	570	220	36.1
	>24	800	570	250	47.8
	SOLAS B	800	570	250	39.5
6	<24	800	570	250	42.4
	>24	800	570	300	57.7
	SOLAS B	800	570	300	45.1
8	<24	800	570	250	47.8
	SOLAS B	800	570	300	50.6
	>24	800	570	300	54.0
10	<24	800	570	300	54.0
12	<24	800	570	300	57.0
GRP CONTAINER DIMENSIONS					
8	>24	820	640	310	65.9
10	>24	820	640	350	77.0
SOLAS B	820	640	350	55.8	
12	>24	820	640	350	84.4
SOLAS B	820	640	350	58.8	

Valise Dimensions

Liferaft size	Pack	Size (mm)			Weight (kg)
		Size (mm)			
4	<24	730	520	320	31.1
	>24	730	520	320	41.6
	SOLAS B	700	500	380	36.2
6	<24	790	500	380	51.1
	>24	800	510	410	60.9
	SOLAS B	860	530	460	47.4
8	<24	790	510	390	41.7
	>24	800	510	410	60.9
	SOLAS B	840	520	450	50.5
10	<24	790	500	380	47.4
	>24	860	530	460	70.9
	SOLAS B	840	520	450	50.5
12	<24	840	520	450	50.5
	>24	860	530	460	70.9
	SOLAS B	840	520	450	50.5